

155 adjustable threaded ball plastic full cone Nozzles



Threaded Nozzle Size

Style No.	Connecting thread size(Inch)	
155	1/4	
	3/8	
	1/2	

Full cone spray tip



Style No.	Flow rate (liters/minute)							Spray angle		
	0.3bar	0.7bar	1bar	1.5bar	2bar	3bar	4bar	0.5bar	1.5bar	4bar
BT6	1.6	2.3	2.6	3.2	3.7	4.5	5.1	69°	74°	68°
BT12.5	3.4	4.8	5.4	6.8	7.7	9.3	10.6	69°	74°	68°
BT25	6.7	9.5	10.9	13.5	15.4	18.6	21	64°	67°	63°

Features:

- Thread screw connection with adjustable full cone spray tips
- Adjustable Ball type tips allow quick and accurate adjustment of spray direction without disturbing pipe connection
- Thread size: 1/4' ' 3/8' ' , 1/2' '
- Orifice Diameter: 2.2mm, 3.2mm, 4.6mm
- Chemical- and corrosion-resistant material PP or FRPP (Fiber reinforced Polypropylene) withstands high temperatures at about 85°C
- General Application :

Metal surface treatment

Pretreatment and rainning test in auto coating industry

Degreasing and phosphating in the process of surface treatment.

Other low pressure washing or cleaning application

Shanghai Xinhou Industrial Co.,Limited

Tel: +86-21-39281563 Fax: +86-21-52240275

Email:info@chinaxinhounozzle.com Website: www.chinaxinhounozzle.com