

PCB Washing Full Cone Quick Dismantling Nozzle



QB



喷头型号 Style No.	流量 (升/分) Flow rate (liters/minute)										喷射角度 Spray angle		
	0.5bar	0.7bar	1.5bar	2bar	3bar	4bar	5bar	6bar	7bar	10bar	0.5bar	1.5bar	6bar
QB2	0.65	0.76	1.0	1.2	1.5	1.7	1.9	2.0	2.2	2.6	43°	50°	46°
QB3	0.98	1.1	1.6	1.9	2.2	2.5	2.8	3.1	3.3	3.9	52°	65°	59°
QB3.5	1.1	1.3	1.9	2.2	2.6	3.0	3.3	3.6	3.9	4.5	43°	50°	46°
QB5	1.6	1.9	2.7	3.1	3.7	4.2	4.7	5.1	5.5	6.5	52°	65°	59°
QB6.5	2.1	2.5	3.5	4.0	4.8	5.5	6.1	6.7	7.1	8.4	45°	50°	46°
QB10	3.3	3.8	5.4	6.2	7.4	8.5	9.4	10.2	11.0	13.0	58°	67°	61°

PCB Washing Full Cone Quick Dismantling Nozzle has the following features:

- With quick dismantling spray tip and quick-change nozzles, the body stays on the header – only the spray tips are replaced which allows you lower costs by changing out just the tips, and slash maintenance time.
- Most Quick dismantling nozzles allow tips to be removed and installed by hand and offer automatic alignment.
- Thread sizes includes 1/4" , 3/8"
- Spray angle from 45 to 65 degrees
- Chemical- and corrosion-resistant material PP or FRPP (Fiber reinforced Polypropylene) withstands high temperatures at about 85°C
- Use with Nitrile or Fluorine rubber as O-ring seal material which is Chemical- and corrosion-resistant
- General Application :

Industrial plating
Etching machine
Development
PCB washing or cleaning
Cooling
Metal finishing
Coating