

Plastic 155 Adjustable Flat Fan Spray Nozzles



155-PP

Fan shaped spray tip



Spray tip style (at 3bar spray angle)						Flow rate (L/min)						
15°	25°	40°	50°	65°	80°	0.3bar	0.7bar	1bar	1.5bar	2bar	3bar	4bar
				CT6505		0.62	0.9	1.1	1.3	1.6	2.0	2.3
				CT6510	CT8010	1.2	1.9	2.3	2.8	3.2	3.9	4.6
		CT4020	CT5020	CT6520	CT8020	2.5	3.8	4.6	5.6	6.5	7.9	9.1
		CT4030		CT6530	CT8030	3.7	5.7	6.8	8.4	9.7	11.8	13.7
		CT4040		CT6540	CT8040	5.0	7.6	9.1	11.2	12.9	15.8	18.2
		CT4050		CT6550		6.2	9.5	11.4	14.0	16.1	19.7	23
		CT4060		CT6560		7.5	11.4	13.7	16.7	19.3	24	27
		CT4070		CT6570		8.7	13.3	16.0	19.5	23	28	32
				CT65100		12.5	19.1	23	28	32	39	46

Plastic 155 Adjustable Flat Fan Spray Nozzles have the following features:

- Material is glass fiber reinforced PP(Polypropylene) with corrosion and wear resistance.
- Plastic 155 Adjustable Flat Fan Spray Nozzles produce a linear spray with spray angle 50° 65° 80° 110°
- Thread size includes 1/4' ' and 3/8' '
- Stable spray angle with uniform, parabolic distribution of liquid.
- Spray pipes equipped with these nozzles show an extremely uniform total distribution of liquid.
- General Application :

Coating pretreatmet

Rinsing

Coating

Washing

Washing

Surface Preparation