

Quick Release Hollow Cone Quick Dismantling Nozzle



Style No.	Flow rate (liters/minute)										Spray angle		
	0.2bar	0.5bar	1bar	1.5bar	2bar	3bar	4bar	5bar	6bar	7bar	0.5bar	1.5bar	6bar
QA3	-	0.97	1.4	1.7	1.9	2.4	2.7	3.1	3.3	3.6	55°	79°	80°
QA5	-	1.6	2.3	2.8	3.2	3.9	4.6	5.1	5.6	6.0	70°	75°	79°
QA8	1.6	2.6	3.6	4.5	5.2	6.3	7.3	8.2	8.9	9.6	65°	72°	74°
QA10	2.0	3.2	4.6	5.6	6.4	7.9	9.1	10.2	11.2	12.1	70°	76°	75°

Quick Release Hollow Cone Quick Dismantling Nozzle has the following features:

- Quick Release Hollow Cone Quick Dismantling Nozzle systems allow you to mix and match bodies and tips to get the exact performance you need.
- Choose polypropylene bodies that easily snap-on the pipe header using a clamp or screw into the pipe header. Both body styles can be installed by hand in seconds without tools. Then, choose your tip style and install, align and position it easily by hand.

• General Application :

Industrial plating
 Etching machine
 Development
 PCB washing or cleaning
 Cooling
 Metal finishing
 Coating