

SJV Three-piece Unijet Flat Fan Spray Nozzles



- SJV Three-piece Unijet Flat Fan Spray Nozzles are easy to assemble and dismantle
- A wide selection of flow rates, spray angles with standard 303,304 Or 316SS materials and connections.
- SJV Three-piece Unijet Flat Fan Spray Nozzles produce a linear spray.
- Spray angle from 0°to 110°
- Thread size range from 1/8' ' to 2' ' with BSPT or NPT thread type
- Stable spray angle with uniform, parabolic distribution of liquid.
- Spray pipes equipped with these nozzles show an extremely uniform total distribution of liquid.
- General Application :

Cleaning

Rinsing

Coating

Washing

Pressure Washing

Surface Preparation

Founded in 2004, XINHOU is a high-tech enterprise with all vitality, potential and comprehensive strength. The company is located in the shanghai, a unique place with beautiful scenery and gifts of nature.

Shanghai Xinhou Industrial Co.,Limited

Tel: +86-21-39281563 Fax: +86-21-52240275

Email:info@chinaxinhounozzle.com Website: www.chinaxinhounozzle.com



Performance Data

Spray angle at 3 bar	Flow code 11001					VEEJET nozzle Nozzle type/inlet connector							Flow (L/min) Spray apple														
		H-1			VVL	H-U U				Equivalent orifice dia.	0.3bar									20bar	35bar	Spray angle					
		•				1/0	2 164	310	1/2	2014	1 11/4 2	0.66	0.12	0.23	0.32	0.39	0.46	0.51	0.56	0.60	0.72	1.0	1.3	94°	110°	121"	12
110°	110015					+						0.79	0.19	0.34	0.48	0.59	0.68	0.76	0.84	0.90	1.1	1.5	2.0	97*	110°	121"	12
	11002											0.91	0.25	0.46	0.64	0.79	0.91	1.0	1.1	1.2	1.4	2.0	2.7	98°	110°	120"	1
	11003	•	•									1.1	0.37	0.68	0.97	1.2	1.4	1.5	1.7	1.8	2.2	3,1	4.0	99"	110°	120"	1
	11004	•	•	•	•							1.3	0.50	0.91	1.3	1.6	1.8	2.0	2.2	2.4	2.9	4.1	5.4	100°	110°	119"	1
	11005 11006	•	:			-	-	\vdash				1.4	0.62	1.1	1.6	2.0	2.3	2.5	2.8	3.0	3.6 4.3	5.1	6.7 8.1	100°	110°	118*	
	11008		÷									1.8	1.0	1.4	2.6	3.2	3.6	4.1	4.5	4.8	5.8	8.2	10.8	102*	110°	117"	
	11010	•	•	-				-	Н			2.0	1.2	2.3	3.2	3.9	4.6	5.1	5.6	6.0	7.2	10.2	13.5	103°	110°	117"	
	11015					+	+	+	\vdash			2.4	1,9	3.4	4.8	5.9	6,8	7.6	8.4	9.0	10.8	15.3	20	104*	110"	117*	
	11020											2.8	2.5	4.6	6.5	7.9	9.1	10.2	11.2	12.1	14.4	20	27	105"	110°	117"	
95"	950050	•										0.46			0.16	0.20	0.23	0.25	0.28	0.30	0.36	0.51	0.67	81"	95*	105*	R
	9501	•	•	•	•							0.66	0.12	0.23	0.32	0.39	0.46	0.51	0.56	0,60	0.72	1.0	1.3	81*	95°	105"	
	95015 9502	•				\vdash	-	+	Н	-	-	0.79	0.19	0.34	0.48	0.59	0.68	1.0	1.1	1.2	1.1	1.5	2.0	82°	95°	105°	-
	9502		÷	•								1.1	0.25	0.68	0.97	1.2	1.4	1.5	1.7	1.8	2.2	3.1	4.0	834	95*	104"	18
	9504											1.3	0.50	0.91	1.3	1.6	1.8	2.0	2.2	2.4	2.9	4.1	5.4	84°	95*	103*	
	9505											1.4	0.62	1.1	1.6	2.0	2.3	2.5	2.8	3.0	3,6	5.1	6.7	84°	95°	102*	1
	9506	•	•									1.6	0.75	1.4	1.9	2.4	2.7	3,1	3.3	3.6	4.3	6.1	8.1	86*	95*	101"	
	9508	•	•	•								1.8	1.0	1,8	2.6	3,2	3.6	4.1	4.5	4.8	5.8	8.2	10.8	87°	95"	100*	12
	9510							-				2.0	1,2	2.3	3.2	3.9	4.6	5.1	5.6	6.0	7,2	10.2	13.5	89"	95°	100°	H
	9515 9520		H					-	•			2.4	1.9	3.4 4.6	4.8 6.5	7.9	6,8 9,1	7,6	11.2	9.0	10.8	15.3	20	90°	95°	100°	
	9530											3.6	3.7	6.8	9.7	11.8	13.7	15.3	16.7	18.1	22	31	40	91"	95°	101°	B
	9540								10.5			4.0	5.0	9.1	12.9	15.8	18.2	20	22	24	29	41	54	92°	95*	100*	
	9550											4.4	6.2	11.4	16.1	19.7	23	25	28	30	36	51	68	93°	95°	99°	
80°	9560											4.8	7.5	13.7	19.3	24	27	31	33	36	43	61	81	93°	95°	99*	
	9570					ш		-				5.2	8.7	16.0	23	28	32	36	39	42	50	70	94	93°	95°	99*	
	95100 95150			H		Н	+					6.4 7.5	12.5	23	32 48	39 59	46 68	76	56 84	90	72 108	102	135	93*	95°	99°	H
	800050						+	+				0.46	10.7	0.11	0.16	0.20	0.23	0.25	0.28	0.30	0.36	0.51	0.67	61°	80*	95°	
	800067			•								0.53		0.15	0.22	0.26	0.31	0.34	0.37	0.40	0.48	0.68	0.90	67*	80*	94*	
	8001											0.66		0.23	0.32	0.39	0.46	0.51	0,56	0,60	0.72	1,0	1,3	681	80°	89°	
	80015	•	•									0.79		0.34	0.48	0.59	0.68	0.76	0.84	0.90	1.1	1.5	2.0	68+	80°	89*	
	8002	•	•									0.91	0.25	0.46	0.64	0.79	0.91	1.0	1.1	1.2	1.4	2.0	2.7	69"	80"	88*	
	8003	•	•	•		-	-	-				1.1	0.37	0.68	1.3	1.2	1.4	1.5	1.7	1.8	2.2	3.1	5.4	70°	80°	87°	H
	8004 8005		:			+	+	+	\vdash		-	1,3	0.62	0.91	1.6	1.6	1.8	2.0	2.2	3.0	2.9	4.1 5.1	6.7	710	80"	86*	+
	8006		•									1.6	0.75	1.4	1.9	2.4	2.7	3.1	3.3	3.6	4.3	6.1	8.1	72°	80°	85°	+
	8008											1.8	1.0	1.8	2.6	3.2	3.6	4.1	4.5	4.8	5.8	8.2	10.8	72"	80°	84°	T
	8010											2.0	1.2	2.3	3.2	3.9	4.6	5.1	5.6	6.0	7.2	10.2	13.5	73°	80"	84°	
	8015											2.4	1.9	3.4	4.8	5.9	6,8	7.6	8.4	9.0	10.8	15.3	20	74°	80°	83*	
	8020											2.8	2.5	4.6	6.5	7.9	9.1	10.2	11.2	12.1	14.4	20	27	74°	80"	83"	H
	8030 8040		-			Н		:				3.6 4.0	3,7 5.0	6.8 9.1	9.7	11.8	13.7	15.3	16.7	18.1	22	31 41	40 54	74°	80°	83*	H
	8050						Ť					4.4	6.2	11.4	16.1	19.7	23	25	28	30	36	51	68	74°	80*	83*	
	8060					+	+					4.8	7.5	13.7	19.3	24	27	31	33	36	43	61	81	75°	80°	83°	t
	8070											5.2	8.7	16.0	23	28	32	36	39	42	50	71	94	75°	80°	83°	
	80100									•		6.4	12.5	23	32	39	46	51	56	60	72	102	138	75"	80*	83°	
	80150						_			•		7.5	18.7	34	48	59	68	76	84	90	108	153	205	73°	80°	84°	
	80200		•					-	Н			8.7	25	46	64	79	91	102	112	121	144	205	270	74°	80"	820	H
	80400 730077	:	:									12.7 0.56	50	91	129	158	182	0.39	0.43	0.46	290 0.55	0.78	1.0	78°	80°	81° 86°	
	730154											0.81	0.19	0.35	0.50	0.61	0.70	0.78	0.86	0.93	1.1	1.6	2.1	55°	73*	84*	
	730231	•	•		•							1.0	0.29	0.53	0.74	0.91	1.1	1.2	1.3	1,4	1.7	2.4	3.1	56°	73°	83°	
	730308		•									1.1	0.38	0.70	0.99	1.2	1.4	1.6	1.7	1.9	2.2	3.1	4.2	581	73*	82"	
	730462						-					1.4	0.58	1.1	1.5	1.8	2.1	2.4	2.6	2.8	3.3	4.7	6.2	601	73°	80°	H
	730770 650017	_					+					1.8 0.28	0.96	1.8	0.05	0.06	0.07	0.08	0.09	0.10	5.5	7.8	10.4	64°	73° 65°	77*	
	650033	-	•			8						0.38			0.00	0.00	0.15	0.17	0.09	0.20	0.12	0.34	0.44	47°	65*	76*	
	650067		•									0.53		0.15	0.22	0.26	0.31	0,34	0,37	0.40	0.48	0.68	0.90	50°	65°	75°	
	6501	•	•		•							0.66		0.23	0.32	0.39	0.46	0.51	0.56	0.60	0.72	1.0	1.3	51°	65°	74°	
	65015	•	•	•	•							0.79	100000	0.34	0.48	0.59	0.68	0.76	0.84	0.90	1.1	1.5	2.0	51"	65°	74*	
	6502	•		•	_							0.91	0.25	0.46	0.64	0.79	0.91	1.0	1.1	1.2	1.4	2.0	2.7	521	65°	73*	
	65025 6503		:									1.0	0.31	0.57	0.81	0.99	1.1	1.3	1.4	1.5	1.8	2.5	3.4	52°	65°	73° 72°	
	6504	•	÷									1.3	0.50	0.91	1.3	1.6	1.8	2.0	2.2	2.4	2.9	4.1	5.4	53"	65"	72°	t
	6505		•	•								1.4	0.62	1.1	1.6	2.0	2.3	2.5	2.8	3.0	3.6	5.1	6.7	53"	65°	72°	
65"	6506		•	•								1.6	0.75	1.4	1.9	2.4	2.7	3.1	3.3	3.6	4.3	6.1	8.1	54°	651	721	
	6508	•	•	•	•							1.8	1.0	1.8	2.6	3.2	3.6	4.1	4.5	4.8	5.8	8.2	10.8	55°	65°	71°	
	6510						_					2.0	1.2	2.3	3.2	3.9	4.6	5.1	5.6	6.0	7.2	10.2	13.5	56°	65*	71°	
	6515							-				2.4	1.9	3.4	4.8	5.9 7.9	6.8	7.6	8.4	9.0	10.8	15.3	20	56°	65°	70°	F
	6520 6530		+	-				-		-		2.8 3.6	3.7	4.6 6.8	6.5 9.7	11.8	9.1	10.2	11.2	12.1	14.4	20	40	57°	65°	69°	-
	6540							- friend				4.0	5.0	9.1	12.9	15.8	18.2	20	22	24	29	41	54	59°	65°	68°	t
	6550							ng-roterio				4.4	6.2	11.4	16.1	19.7	23	25	28	30	36	51	68	60°	65°	684	
	6560					1						4.8	7.5	13.7	19.3	24	27	31	33	36	43	61	81	60°	65°	68"	
	6570											5.2	8.7	16.0	23	28	32	36	39	42	50	71	94	60°	65*	681	
	65100							•				6.4	12.5	23	32	39	46	51	56	60	72	102	135	581	65°	69°	
	65150 65200											7.5 8.7	18.7 25	34 46	48 64	59 79	68 91	76 102	112	90	108	153 205	205	59°	65°	68°	

Shanghai Xinhou Industrial Co.,Limited

Tel: +86-21-39281563 Fax: +86-21-52240275

Email:info@chinaxinhounozzle.com Website:www.chinaxinhounozzle.com