

Stainless Steel Quick VeeJet Flat Fan Spray Nozzles



QJV

Quick connect header



O-Ring



Quick connect body



- Stainless Steel Quick VeeJet Flat Fan Spray Nozzles are easy to assemble and dismantle
- Internal O-ring provides a positive seal between the body and tip; seal remains attached to tip eliminating accidental loss
- A wide selection of flow rates, spray angles with standard 303,304 Or 316SS materials and connections.
- Stainless Steel Quick VeeJet Flat Fan Spray Nozzles produce a linear spray.
- Spray angle from 0°to 110°
- Thread size range from 1/8' ' to 2' ' with BSPT or NPT thread type
- Stable spray angle with uniform, parabolic distribution of liquid.
- Spray pipes equipped with these nozzles show an extremely uniform total distribution of liquid.
- General Application :

Cleaning

Rinsing

Coating

Washing

Pressure Washing

Surface Preparation

Established in 2004, XINHOU is a professional manufacturer and exporter that is concerned with the design, development and production of Stainless Steel Quick VeeJet Flat Fan Spray Nozzles. We are located in shanghai, with convenient transportation access. All of our products comply with international quality standards and are greatly appreciated in a variety of different markets throughout the world.

Our well-equipped facilities and excellent quality control throughout all stages of production enables us to guarantee total customer satisfaction.

If you are interested in any of our product or would like to discuss a custom order, please feel free to contact us. We are looking forward to forming successful business relationships with new clients around the world in the near future.

Spray angle at 3 bar	Flow code	VEEJET nozzle Nozzle type/Inlet connector												Flow (L/min)											Spray angle			
		H-VV		H-VVL		H-U			U		Equivalent orifice dia.																	
		1/8	1/4	1/8	1/4	1/8	1/4	3/8	1/2	3/4		1	1-1/4	2	0.3bar	1bar	2bar	3bar	4bar	5bar	6bar	7bar	10bar	20bar	35bar	1.5bar	3bar	6bar
15°	1560					●	●						4.8		13.7	19.3	24	27	31	33	36	43	61	81	11°	15°	18°	21°
	1570					●	●						5.2		16.0	23	28	32	36	39	42	50	71	94	11°	15°	18°	21°
	15100						●	●					6.4	12.5	23	32	39	46	51	56	60	72	102	135	13°	15°	17°	18°
	15120						●						6.7	15.0	27	39	47	55	61	67	72	86	122	162	13°	15°	17°	18°
	15150							●					7.5	18.7	34	48	59	68	76	84	90	108	153	205	14°	15°	17°	18°
	15200								●				8.7	25	46	64	79	91	102	112	121	144	205	270	14°	15°	17°	18°
	15250									●			9.5	31	57	81	99	114	127	140	151	180	255	340	14°	15°	16°	17°
	15500										●		13.1	62	114	161	197	230	255	280	300	360	510	680	14°	15°	16°	17°
	151000											●	18.7	125	230	325	395	455	510	560	610	720	1020	1350	14°	15°	16°	17°
	0°	0003					●	●					1.0	0.37	0.68	0.97	1.2	1.4	1.5	1.7	1.8	2.2	3.1	4.0				
0004						●	●					1.2	0.50	0.91	1.3	1.6	1.8	2.0	2.2	2.4	2.9	4.1	5.4					
0005						●	●					1.3	0.62	1.1	1.6	2.0	2.3	2.5	2.8	3.0	3.6	5.1	6.7					
0006						●	●					1.5	0.75	1.4	1.9	2.4	2.7	3.1	3.3	3.6	4.3	6.1	8.1					
0008						●	●					1.7	1.0	1.8	2.6	3.2	3.6	4.1	4.5	4.8	5.8	8.2	10.8					
0010						●	●					1.9	1.2	2.3	3.2	3.9	4.6	5.1	5.6	6.0	7.2	10.2	13.5					
0015						●	●					2.3	1.9	3.4	4.8	5.9	6.8	7.6	8.4	9.0	10.8	15.3	20					
0020						●	●	●				2.7	2.5	4.6	6.5	7.9	9.1	10.2	11.2	12.1	14.4	20	27					
0030						●	●					3.6	3.7	6.8	9.7	11.8	13.7	15.3	16.7	18.1	22	31	40					
0040						●	●					4.0	5.0	9.1	12.9	15.8	18.2	20	22	24	29	41	54					
0050						●						4.4	6.2	11.4	16.1	19.7	23	25	28	30	36	51	68					
0060						●						4.8	7.5	13.7	19.3	24	27	31	33	36	43	61	81					
0070						●	●					5.2	8.7	16.0	23	28	32	36	39	42	50	71	94					
0080						●	●					5.2	10.0	18.2	26	32	36	41	45	48	58	82	108					
00100							●					6.0	12.5	23	32	39	46	51	56	60	72	102	135					
00120							●					6.4	15.0	27	39	47	55	61	67	72	86	122	162					
00150								●				7.5	18.7	34	48	59	68	76	84	90	108	153	205					
00200									●			8.3	25	46	64	79	91	102	112	121	144	205	270					
00250								●				9.5	31	57	81	99	114	127	140	151	180	255	340					
00350										●		11.1	44	80	113	138	160	178	195	210	255	360	475					
00700											●	15.5	87	160	225	275	320	355	390	420	510	720	950					
001000												19.1	125	230	325	395	460	510	560	610	720	1020	1350					
001100												19.8	140	255	355	435	500	560	620	670	790	1120	1490					
001400												22.2	175	320	455	560	640	720	780	850	1010	1430	1890					
001800												25.4	225	410	580	710	820	920	1010	1090	1300	1840	2430					
002000											26.6	250	460	650	790	910	1020	1120	1210	1440	2040	2700						
003500											34.9	440	800	1130	1380	1600	1790	1960	2110	2520	3570	4720						

0°
液柱流

