

ZSTM Water Curtain Flat Fan Spray Nozzles



ZSTM

Style No.	Pressure (MPa)	Flow rate (L/min)	K Factor (K)	Spray Angle (°)	Thread Size
ZSTM8	0.35	15	8	45° 60° 90° 120° 150°	1/2" 3/4" 1"
ZSTM10		18.5	10		
ZSTM14.9		28	14.9		
ZSTM17		32	17		
ZSTM21.4		40	21.4		
ZSTM27		50	27		
ZSTM28		52	28		
ZSTM40		75	40		
ZSTM52		97	52		
ZSTM80		150	80		
ZSTM115		215	115		

ZSTM Water Curtain Flat Fan Spray Nozzles have the following features:

- ZSTM Water Curtain Flat Fan Spray Nozzles quickly form a water curtain
- It is used as a fire proof or partial cooling or protection, limit burning speed, reduce fire damage, reduce explosion risk, and promote vapor dilution and emission.
- It is usually installed in the opening of the floor or places of warehouse such as liquefied petroleum and chemical products.
- It is often used together with protective roller blinds and glass curtain walls
- ZSTM Water Curtain Flat Fan Spray Nozzles have the functions of cooling, suffocating, emulsifying, diluting, and insulating to achieve the suppression of fire and fire extinguishing.
- Spray angle from 45° to 120°
- Thread size : 1/2" , 3/4" , 1" , 2"